

L40

Vertical Mount Kynar Plastic Liquid Level Switch

OVERVIEW

The Whitman Controls L40 Series Vertical Mount Kynar Plastic Liquid Level Switches are light-weight levels typically used in solvents and certain bases. The switch can be subjected to 100 PSIG and the Red Seal potting makes the switch submersible to a NEMA 6 rating. They can be applied to numerous O.E.M. and various other industrial applications and are available with a number of options.

KEY FEATURES

- Red Seal potting submersible to a NEMA 6 rating
- Kynar Plastic
- Extensive operating temperature range
- SPST availability

SPECIFICATIONS

- **Wetted Materials:** Kynar – White
- **Minimum Liquid Specific Gravity:** 1.00
- **Liquid Temperature range:** -40°F to +180°F
- **Max System Pressure:** 100 PSIG
- **Electrical Switch Rating:** 50 VA
- **Weight:** 5.0 oz (approx.)

PERFORMANCE CHARACTERISTICS

	L40 Series
Fitting	1/8" NPT
Wetted Materials	Kynar
Electrical Switch Rating	50 VA
Temperature Range	-40°F to +180°F
Minimum Liquid Specific Gravity	1.00
Crush Pressure	100 PSI
Lead Wires	20 AWG 24" PVC
Part Number	L40-17-C1-17-NO

*Actuation point is roughly midway of float travel in liquid with a specific gravity of approximately 1.0

CAUTION: Customer Media and environment must be compatible with construction materials as outlined above

